DECLARATION OF PERFORMANCE
No. 0012-DoP-2023/02/13

CE

FLOOR 190

MW-EN13162-T5-DS(70,90)-CS(10)70-TR15-PL(5)700-WS-WL(P)-AW0,80-MU1

1. Unique identification code of the product-type: **FLOOR 190**
2. Intended use: **Thermal insulation products for buildings – Factory made mineral wool (MW) products. For uses subject to regulations on reaction to fire A1.**
3. Manufacturer: **Joint Stock Company «GomelStroyMaterialy» Republic of Belarus, Mogilevskaya str., 14, 246010 Gomel**
4. Authorized representative: -
5. System of attestation of conformity: **System 1, System 3**
6. Harmonized standard: **EN 13162:2012+A1:2015**
   Notified certification body: No. 1020 performed Certificate of constancy of performance No. 1020 –CPR-010022606
   Report of the assessment of performance No. 1020-CPR-010-044681.

7.Declared Performance		
Essential Characteristics	**Clauses in this and other European standard(s) related to essential characteristics**	**Harmonized standard**
Reaction to fire	Reaction to fire Euroclasses **A1**	**EN 13162:2012+A1:2015**
Release of dangerous substances to the indoor environment	Release of dangerous substances EU level not yet available **NPD**	
Acoustic absorption index	Sound absorption αp(APi) and αw(AWi) declared **AW0,80**	
Impact noise transmission index (for floors)	Dynamic stiffness s' SD deklarowane **NPD**	
	Thickness, d_L d_L and classes for thickness tolerances T6 lor T7 **NPD**	
	Compressibility c CPi declared **NPD**	
	Airflow resistivity AF_r i declared **NPD**	
Direct airborne sound insulation index	Airflow resistivity AF_r i declared **NPD**	
Continuous glowing combustion	Continuous glowing combustion EU level not yet available **NPD**	
Thermal resistance	Thermal resistance and thermal conductivity Thermal conductivity λ (W/mK) **0,040** Thermal resistance R = d / λ (m^2K/W) **0,75÷3,75. See tabel**	
	Thickness Thickness range (mm) **30 – 150** Ti class for thickness tolerance **T5**	
Water permeability	Short term water absorption WS declared WP; kg/m^2 **WS**	
	Long term water absorption WL(P) - declared W IP;kg/m^2 **WL(P)**	
Water vapour permeability	Water vapour transmission Declared μ; (MUi) or Zi **MU1**	
Compressive strength	Compressive stress or compressive strength CS(10)i or CS(10/Y)i declared (kPa) **CS(10)70**	
	Point load PL(5)i declared (N) **PL(5)700**	
Durability of reaction to fire against heat, weathering, ageing\degradation	Durability characteristics Euroclasses **A1**	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity Declared R = d / λ (m^2K/W) **0,75÷3,75. See tabel** Declared λ W/mK **0,040**	
	Durability characteristics DS(70) declared. The relative changes in thickness **NPD** DS(70,90) declared. The relative changes in thickness **DS(70,90)**	
Tensile strength	Tensile strength perpendicular to faces TRi declared (kPa) **TR15**	
Durability of c ompressive strength against ageing\degradation	Compressive creep CC(i1/i2)δc compressive creep declared X_{ct} and X_t **NPD**	

Thermal resistance R_D													
d (mm)	30	40	50	60	70	80	90	100	110	120	130	140	150
R_D m²K/W	**0,75**	**1,00**	**1,25**	**1,50**	**1,75**	**2,00**	**2,25**	**2,50**	**2,75**	**3,00**	**3,25**	**3,50**	**3,75**

8. The Characteristics of the product specified above correspond to the declared characteristics. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

13 February 2023
General Director Joint Stock Company «GomelStroyMaterialy» Stanisiav Zeromski

Joint Stock Company «GomelStroyMaterialy»,
Republic of Belarus, Mogilevskaya str., 14, 246010 Gomel
www.oaogsm.by
e-mail: info@gstrmat.by
tel./faks: +375 232 59 51 18